



SFE Series IV

There Are Some Things You Can Always Depend

On








SFE IV

82% AFUE Oil Fired Steam Boiler

- Available in 4 sizes from 106 MBH to 247 MBH.
- Dependable Cast Iron Heat Exchanger with Cast Iron Push Nipples. The Sections and Push Nipples expand at the same rate when heated. By using similar materials instead of less expensive gaskets the boiler maintains a water tight seal over time.
- Patented Protective Heat Shield Baffle to protect the casting above the water line.
- Honeywell Pressure Control, Boiler Water Level Gauge Glass, and Steam Pressure Gauge.
- Electronic Low Water Cutoff.
- Atmospheric Chimney Vent Boiler.
- Textured paint Jacket with compact footprint.
- Cast Iron swing door and large flueways allow for easy cleaning and servicing.
- 10 Year Limited Warranty (Residential Applications).
- Made in the U.S.A.



Utica SFE Series IV Residential Oil Fired Steam Boiler

Dimensional Diagram	Model		AHRI Oil Burner Input ⁽¹⁾		Htg. Cap. MBH ⁽⁴⁾	Net AHRI Ratings ⁽³⁾		Min. Nat. Draft Chimney Size		Pump Press. PSI	Nozz. Furn.	AFUE %										
			G.P.H.	MBH ⁽²⁾		Steam MBH	Sq. Ft. Steam	Round	Square													
<div>Front View</div>  <div>Side View</div> 	Without Tankless	SFE-3090S	0.90	126	106	80	333	6"	8"x8"x15'	150	0.75-60°B	82.0%										
		SFE-4125S	1.25	175	147	110	458	6"	8"x8"x15'	140	1.10-60°B	82.0%										
		SFE-5185S	1.85	259	216	162	675	8"	8"x8"x15'	150	1.50-70°B	82.0%										
		SFE-6210S	2.10	294	247	185	771	8"	8"x8"x15'	145	1.75-70°B	82.0%										
	With Tankless	SFE-3090ST	0.90	126	106	80	333	6"	8"x8"x15'	150	0.75-60°B	82.0%										
		SFE-4125ST	1.25	175	147	110	458	6"	8"x8"x15'	140	1.10-60°B	82.0%										
		SFE-5185ST	1.85	259	216	162	675	8"	8"x8"x15'	150	1.50-70°B	82.0%										
		SFE-6210ST	2.10	294	247	185	771	8"	8"x8"x15'	145	1.75-70°B	82.0%										
	(1) Burner input is based on an oil heating value of 140,000 Btu/gal.																					
	(2) MBH = 1000 Btu per hour [Btu = British Thermal Unit].																					
	(3) Net AHRI Steam Ratings based on piping and pick-up allowance of 1.333. Consult manufacturer before selecting boiler for installations having unusual piping and pick-up requirements, such as intermittent system operation, extensive piping, etc.																					
	(4) Electrical service is 120 Volts, 15 Amps, 60 Hz.																					
General Information (See Installation, Operation and Maintenance Manual for complete instructions)																						
Clearances Required distances measured from boiler.	Top					Combustible Materials (Required)																
						24" (610 mm)																
						Left Side (Control Side)					6" (152 mm)											
											Right Side					24" (610 mm)						
																Front					24" (610 mm)	
																					Back	
Flue Connector					9" (229 mm)																	
Connections (All Models)		Supply Tapping Two 2", Return Tapping 1-1/2", Oil Line 3/8" O.D. copper tubing for runs of 50 feet or less, and 1/2" O.D. for longer runs.																				
Electrical		120 Volts AC, 60 hertz, 1 phase, Less than 12 amps (15 amp circuit recommended).																				
Tankless Heater Capacities	Model	Input Rate G.P.H.	Tankless Heater Number	Tankless Heater Capacity Intermittent Draw G.P.M.	Boiler Water Content (Gallons)																	
					L-24	2	11	8														
									4 1/2	13	9											
												4 1/2	15	10								
															4 1/2	15	10					
Dimensions/Weights	No. of Sec.	A (Length of Flush Jacket)		B (Front of Jacket to Center Line of Flue Outlet)		C (Flue Outlet Diameter)		Weight														
	3	16 3/8"		6 1/2"		6"		534 lbs.														
	4	20 1/4"		8 1/2"		6"		688 lbs.														
	5	23 5/8"		10 1/4"		7"		781 lbs.														
	6	27 1/2"		8 5/16"		8"		901 lbs.														
Standard Equipment		Boiler Controls: Honeywell Pressuretrol, Boiler Water Level Gauge Glass, and Steam Pressure Gauge. Heat Exchanger: Cast Iron Heat Exchanger with Cast Iron Push Nipples, Swing Door. Combustion: Beckett Oil Burner, Target Wall/Liner. Electrical: Wiring Harness, Burner Electric Disconnect. Safety: Electronic Low Water Cut Off. Other: Crated Boiler, Flush Jacket, ASME Relief Valve, Drain Valve, Plastic Cover, Two 2" Supply Tappings, 1-1/2" Return Tapping and Skim Port. For Tankless Heater Units: Add Tankless Hot Water Coil and 4006 Limit Control.																				
Options		Taco or Grundfos; Tankless Coil.																				
Certifications		<div></div> <div>Tested for 15 psi ASME Working Pressure</div>																				

All ratings and specifications subject to change.

PN 240009857 Rev. 8/13

Contractor Assistance: 800.325.5479



P.O. Box 4729
Utica, New York 13504
tel: 315.797.1310 • fax: 315.797.3762
www.utica boilers.com

