



MGB Series II/MGC Series

There Are Some Things You Can Always Depend On...



MGB II / MGC

Up to 83.9% AFUE Gas Fired Hot Water Boiler

- Available in 9 sizes from 50 MBH to 299 MBH.
- Dependable Cast Iron Heat Exchanger with Cast Iron Push Nipples. The Sections and Push Nipples expand at the same rate when heated. By using similar materials instead of less expensive gaskets the boiler maintains a water tight seal over time.
- Honeywell High Limit/Electronic Ignition Control.
 - With durable protective cover and viewing window.
 - Digital temperature display and diagnostics.
 - Plug in connection for the vent damper.
 - Plug in connection for the system pump.

Control monitors water temperature and delays the burner starting until and residual heat has been transferred. This maximizes efficiency by turning on the burner only when needed.

- Atmospheric Chimney Vent Boiler with Integral Draft Hood and Automatic Vent Damper. The Integral Draft Hood reduces the overall height and footprint of the boiler making it ideal for low clearance/space limited installations.
- Textured paint Jacket.
- Limited Lifetime Warranty (Residential Applications)
- Made in the USA



MGB Model Shown

Utica MGB Series II & MGC Series Gas Fired Hot Water Boiler

Dimensional Diagram	Model	Input Rate (MBH) ⁽¹⁾	Heating Capacity (MBH) ⁽¹⁾	Net AHRI Rating, Water (MBH) ⁽²⁾	Air Cushion Tank ⁽³⁾	No. of Burners	AFUE %
MGB Front 	MGB-50J	50	52	36.3	15	1	83.5%
	MGB-75J	75	63	54.8	15	2	83.1%
	MGB-100J	100	83	72.0	30	2	83.0%
	MGB-125J	125	104	90.0	30	3	82.0%
	MGB-150J	150	124	107.8	30	3	83.0%
	MGB-170J	170	139	121.0	30	4	82.0%
	MGB-200J	200	165	143.4	30	4	82.0%
	MGC-8D/DP*	262.5/245	220/206	191.0/179.0	60	7	83.9%
	MGC-9D/DP*	299/280	251/235	218.0/204.0	60	8	83.7%
	*D=Natural Gas, DP=LP Gas The MGC has distinct input rates for Natural and LP gas versions. 8D/9D rates shown are for Natural gas. 8DP/9DP rates are for LP gas. (1) Input rating for sea level to 2,000 ft. (610m) above sea level. United States, over 2000 ft (610m) above sea level. Reduce input rate 4% for every 1000 ft (304m) above sea level. (2) Net AHRI Water Ratings shown based on piping and pickup allowance of 1.15. Consult manufacturer before selecting boiler for installations having unusual piping and pickup requirements, such as intermittent system operation, extensive piping systems, etc. For forced hot water systems where boiler and all piping within area to be heated, boiler may be selected on basis of its heating capacity. (3) Recommended tank sizes for non-ferrous baseboard or radiant panel systems. Increase size for cast iron baseboard and radiation.						
MGB Side 	General Information (See Installation, Operation and Maintenance Manual for complete instructions)						
	Clearances (4) Required distances measured from boiler. *Definition of Alcove is three sided space with no wall in front of boiler. ANSI standard for alcove is 18 inches from appliance to leading edge of side walls as shown in IOM.	Combustible Materials (Required) ⁽⁴⁾		MGB		MGC	
				Top		18" (457 mm)	
		Left Side		3" (76mm)		6" (152 mm)	
		Right Side (Control Side)		9" (229 mm)		7" (178 mm)	
		Front		Alcove*		18" (457 mm)	
		Back		4" (102 mm)		6" (152 mm)	
		Flue Connector		6" (152 mm)		6" (152 mm)	
		Connections (All Models)		Return/Supply Water 1-1/4", Gas In 1/2" NPT			
	Electrical		120 Volts AC, 60 hertz, 1 phase, Less than 12 amps (15 amp circuit recommended)				
Water Content		50 - 2.4 Gallons, 75/100 - 4.0 Gallons, 125/150 - 5.6 Gallons, 170/200 - 7.2 Gallons, 262.5 - 12.7 Gallons, 299 - 14.4 Gallons					
MGC Front 	Dimensions/Weights	Model	A	B	C	D	Weight
		MGB-50J	11-1/8"	4"	30-3/4"	36-1/4"	205 lbs.
		MGB-75J	15"	5"	30-3/4"	37-3/4"	253 lbs.
		MGB-100J	15"	6"	30-3/4"	37-1/4"	253 lbs.
		MGB-125J	18-7/8"	6"	30-3/4"	37-1/4"	315 lbs.
		MGB-150J	18-7/8"	7"	30-3/4"	37-3/4"	315 lbs.
		MGB-170J	22-3/4"	7"	30-3/4"	38-3/4"	377 lbs.
		MGB-200J	22-3/4"	8"	30-3/4"	38-3/4"	377 lbs.
		Model	A	C	D	E	Weight
		MGC-8D/DP	27-1/2"	7"	36-3/8"	43-1/8"	552 lbs.
MGC-9D/DP	30-3/4"	7"	36-3/8"	43-1/8"	616 lbs.		
MGC Side 	Standard Equipment Boiler Control Module: Honeywell Control (High Limit/Electronic Ignition Control) with plastic cover and display window. User Display Interface: Digital Temperature Display Heat Exchanger: Cast Iron Sections with Cast Iron Push Nipples. Combustion: Stainless Steel Main Gas Burners (MGB)/Titanium Composite Burners (MGC), Combination 24 Volt Gas Control (Includes: Automatic Gas Valve, Gas Pressure Regulator, Automatic Pilot, Safety Shutoff, Pilot Flow Adjustment, Pilot Filter), Intermittent Pilot Control, Continuous Retry, Combination Pilot Burner/Electrode/Flame Sensor. Safety: Spill Switch and Roll-Out Switch for safety (MGB)/Flame Roll-Out Safety Shut-Off (Fuse Link) (MGC), Automatic Vent Damper. Other: Insulated Boiler Jacket, Integral Draft Diverter, Combination Temperature/Pressure Gauge, Circulator Pump, 3/4" Drain Valve, 30lb. ASME Relief Valve.						
	Options Available in both natural gas or propane models. Central Heating Pump (Taco, Grundfos, B&G or Less Pump), LP Conversion Kit, Combustible Floor Plate, Fill-Trol.						
Certifications C.S.A. Certified For Natural Gas Or Propane US Tested for 100 psi (MGB) / 50 psi (MGC) ASME Working Pressure www.ahridirectory.org							

All ratings and specifications subject to change.

PN 240009709 Rev. 10/13

Contractor
Assistance: 800.325.5479



P.O. Box 4729
Utica, New York 13504
tel: 315.797.1310 • fax: 315.797.3762
www.uticaboilers.com

