



SSC 
STAINLESS STEEL CONDENSING

There Are Some Things You Can Always Depend On...

Founder



SSC

Up to 95% AFUE Gas Fired, Wall Hung
Modulating Condensing Boiler

- Built-In Primary/Secondary Piping cuts installation time in half
- Built-In Low Water Cut Off
- 5:1 Turn Down Ratio
- Original Heat Exchanger
 - Low Maintenance, Self-Cleaning
 - Designed in the U.S., for the U.S.
 - 150 psi MAWP



**Most Efficient
2014**
www.energystar.gov





The Utica SSC "Stainless Steel Condensing" high efficiency, wall hung modulating boiler features a unique 316L/444 stainless steel heat exchanger designed in the U.S., for the U.S. This vertically mounted heat exchanger features wide, smooth water ways that help remove hard water deposits and prevent scaling which ultimately means longer life and better value.

Utica Boilers has been keeping generations warm since 1928. We take pride in having grown up right alongside the generations we serve with products that continue to meet your ever changing needs. That's why we have added a 299 MBH capacity to our SSC offering and introduced the H2O Series - a full line of Stainless Steel, Single and Dual Coil Indirect Water Heaters, Buffer Tanks and Storage Tanks. A Utica SSC and an H2O Stainless Steel Indirect Water Heater are the perfect match.



Just look at what you could be saving annually...

Add up the savings with a Utica SSC:

- + Up to 95% AFUE
- + Sealed Combustion
- + Outdoor Temperature Reset*

The increased efficiency of the SSC could save you up to 40% on your heating bill each year.

If you pay \$1,800 annually to heat your home, you could save as much as \$720 per year.

That's \$3,600 over 5 years!**

* A factory standard Outdoor Temperature Reset adjusts water supply temperature for best possible fuel economy based on actual seasonal conditions.

** Individual savings may vary.

- ▶ Utica H2O Indirect Water Heaters are available in 30 to 150 gallon capacities and also feature 316L stainless steel construction as well as top connections for ease of installation. In terms of efficiency, the H2O is so well insulated that water will lose only a half degree for every hour on standby. Like the SSC, the H2O's smooth coil design prevents corrosion so it is also an excellent value.
- ▶ Each Utica SSC boiler produced is subjected to a rigorous set of quality control checks before it leaves our factory. Utica test fires each boiler and checks all of the electrical, plumbing, pressure vessel and combustion set up parameters - fine tuning the product's performance prior to approving the unit for shipment. We even include the final computer generated results for your professional contractor to reference while completing your installation.
- ▶ Since we go the extra mile to deliver a quality product we offer not only a 15 year limited manufacturer's warranty, we also back it up with an industry-leading first year \$500 Heat Exchanger Labor Warranty.
- ▶ Our H2O Single Coil Indirect Water Heaters feature a limited lifetime warranty and optional Comfort Plus Parts & Labor warranties are available for all our products.





SSC 50-200 MBH



Integral Condensate Trap ▲

- Large Diameter
- Quick connect to condensate drain or pump

Heat Exchanger



- 316L/444 stainless steel fin tube
- Vertically mounted
- Self-cleaning
- Designed in the U.S., for the U.S.
- 150 psi MAWP

Non-Metallic Flue Collector



- Corrosion resistant

LWCO



- Factory wired and installed
- Probe-type with test button
- Meets code where required
- Provides added protection

Control Features



- 5:1 Turn down ratio
- Easy to understand English text display
- Outdoor reset maximizes fuel economy
- Priority domestic hot water meets changing demands
- Integrated multiple boiler control eliminates the need for costly multiple boiler controls
- Can be remotely mounted with standard thermostat conductor wiring

Quick Connect



- Simplified electrical connection and removable terminal block make wiring easy

Top Connections



- Approved for PVC, CPVC and Polypropylene venting

Bottom Connections



- Replacement ready with 1-1/4" piping connections and low pressure drop
- No high head pump required

Wall Mount Bracket



- Bracket included
- Wall mount installation saves space

SSC 299 MBH







299 Dual Diameter Heat Exchanger with polypropylene flue collector



- 316L/444 stainless steel fin tube
- Vertically mounted
- Self-cleaning
- Designed in the U.S., for the U.S.
- 150 psi MAWP

► Built-in primary/secondary piping on all models saves installation time and space

Utica SSC Natural or Propane Gas-Fired Modulating Condensing Hot Water Boiler

Dimensions/Weights	Model	Boiler Input Rate (MBH) ⁽¹⁾		Heating Capacity (MBH) ⁽¹⁾⁽²⁾	Net AHRI Rating, Water (MBH) ^{(1) (3)}	AFUE % ⁽²⁾	
		Max.	Min.				
	UBSSC-050	50	10	46	40	95.0	
	UBSSC-075	75	15	69	60	95.0	
	UBSSC-100	100	20	91	79	95.0	
	UBSSC-150	150	30	139	121	95.0	
	UBSSC-200*	200	40	185	161	94.0	
	UBSSC-299*	299	60	273	239	94.0	
* The UBSSC-200 and UBSSC-299 have an AFUE of 94% and are ENERGY STAR rated products but they do not meet the 95% criteria for 2014 Most Efficient.							
(1) 1000 Btu/hr (British Thermal Units Per Hour)							
(2) Heating Capacity and AFUE (Annual Fuel Utilization Efficiency) are based on DOE (Department of Energy) test procedures.							
(3) Net AHRI Ratings based on piping and pickup allowance of 1.15. Contact Technical Support before selecting boiler for installations having unusual piping and pickup requirements, such as intermittent system operation, extensive piping systems, etc.							
General Information (See Installation, Operation and Maintenance Manual for complete instructions)							
	Clearances (4) Required distances measured from boiler. (5) Service, proper operation clearance recommendation.	Top	Combustible Materials (Required) ⁽⁴⁾			Service ⁽⁵⁾	
		Left Side	0" (0 cm)			14" (36 cm)	
		Right Side	0" (0 cm)			0" (0 cm)	
		Front	0" (0 cm)			6" (16 cm)	
		Back	0" (0 cm)			0" (0 cm)	
		Bottom	0" (0 cm)			12" (32 cm)	
		Combustion Air/Vent Piping	0" (0 cm)			6" (16 cm)	
		Hot Water Piping	See Local Code			6" (16 cm)	
	Combustion Air & Vent Pipe Equivalent Length (Schedule 40 PVC)	2" Pipe 050	2" Pipe 075/100	3" Pipe 075/100	3" Pipe 150/200	3" Pipe 299	4" Pipe 299
		6 Ft. (1.8 m)	6 Ft. (1.8 m)	6 Ft. (1.8 m)	6 Ft. (1.8 m)	6 Ft. (1.8 m)	6 Ft. (1.8 m)
		100 Ft. (30.5 m)	50 Ft. (15.2 m)	100 Ft. (30.5 m)	100 Ft. (30.5 m)	25 Ft. (7.7 m)	100 Ft. (30.5 m)
		Note: Refer to IOM and vent pipe manufacturer's instructions for equivalent vent lengths and alternate venting materials.					
	Connections	Return/Supply Water		Gas In		Condensate Drain	
	050/075/100	1-1/4" NPT		1/2" NPT		3/4" NPT	
	150/200/299	1-1/4" NPT		3/4" NPT		3/4" NPT	
Electrical	120 Volts AC, 60 hertz, 1 phase, Less than 12 amps (15 amp circuit recommended)						
Water Content	050/075/100 - 1.1 Gallons, 150/200/299 - 1.8 Gallons						
Dimensions		Standard Equipment					
Models	050 075 100	150 200	299				
Width (A)	20" 508 mm	23" 584 mm					
Height (B)	30" 762 mm	41" 1041 mm					
Depth (C)	14" 356 mm	16" 406 mm	18.3" 465 mm				
Bracket (D)	28" 711 mm	40" 1016 mm					
HLW/Piping (E)	31" 787 mm	42" 1092 mm					
Weights		Options					
Ship Wgt.	111 lbs. 50 kg	~182 lbs. 83 kg	~225 lbs. 102 kg				
Boiler Wgt.	91 lbs. 41 kg	~157 lbs. 71 kg	~195 lbs. 89 kg				
Certifications		Central Heating Pump available for 50 to 200 MBH only (Taco 007 or Grundfos UP15-42F), Concentric Vent Kit (2" and 3"), System Sensor (For Multiple Boiler Applications)					
150 psi MAWP		ASME H					
AHRI CERTIFIED		www.ahridirectory.org					

Dimensions			
Models	050 075 100	150 200	299
Width (A)	20" 508 mm	23" 584 mm	
Height (B)	30" 762 mm	41" 1041 mm	
Depth (C)	14" 356 mm	16" 406 mm	18.3" 465 mm
Bracket (D)	28" 711 mm	40" 1016 mm	
Ht w/Piping (E)	31" 787 mm	42" 1092 mm	
Weights			
Ship Wgt.	111 lbs. 50 kg	~182 lbs. 83 kg	~225 lbs. 102 kg
Boiler Wgt.	91 lbs. 41 kg	~157 lbs. 71 kg	~195 lbs. 89 kg

PN 240008985 Rev 2/14



P.O. Box 4729
Utica, New York 13504

Tel: 315.797.1310
Fax: 315.797.3762

Contractor Assistance:
800.325.5479

  
www.uticaboilers.com