



There Are Some Things You Can Always Depend On...



Utica H₂O

- Stainless Steel Single Coil Indirect Water Heaters
- Stainless Steel Storage Tanks
- Stainless Steel Hydronic Buffer Tanks
- Stainless Steel Single and Dual Coil Solar Water Heaters



THE UTICA H₂O SERIES

A complete line of Stainless Steel, Single and Dual Coil Indirect Water Heaters, Storage Tanks, and Hydronic Buffer Tanks.

Need An Easy Domestic Hot Water Solution With A Low Operating Cost and the Longevity Of Stainless Steel?

Utica H₂O Stainless Steel Single Coil Indirect Water Heaters

Need A Hot Water Solution To Balance Input and Storage While Reducing Short Cycling?

Utica H₂O Stainless Steel Storage Tanks

Need A Hot Water Solution For Use With Chillers, Heat Pumps, and Low Mass Boilers?












Utica H₂O Stainless Steel Hydronic Buffer Tanks

Need A Hot Water Solution For Solar Applications Or Small Zones?

Utica H₂O Stainless Steel Single & Dual Coil Solar Water Heaters

(Optional Electric Back-Up can heat the tank if solar heat is unavailable)

**Stainless Steel
Single Coil Indirect
Water Heaters**

STANDARD FEATURES	
Capacities (Gallons)	30, 40, 40L, 50 , 60, 60L, 80, 85* & 115
316L Stainless Steel Construction	
Top Connections (For Easy, Neat, Clean Installation)	
Welded Stainless Steel Dip Tube (Factory installed)	
Thermoplastic Jacket (Won't dent, scratch or corrode)	
Low Pressure Drop (Ideal For Low Mass Boilers)	
Magnesium Anode Rod	
T & P Valve, Stainless Aquastat Well & Drain Valve (Factory installed-taped and doped).	
2.25" EPS Insulation (Provides Less Than .5°F Per Hour Standby Loss)	
Large Diameter, Smooth Coil Heat Exchangers - Prevent Buildup (Stainless Steel Coils Are 25 to 30' Long and 1-1/8" in Diameter)	
Honeywell L4080B (Shipped Loose)	
Made in the USA	
WARRANTY	
Limited Lifetime Warranty (Residential), 5 Yr. (Commercial)	
Limited Lifetime Warranty	N/A
OPTIONS	
Low Profile	40L & 60L Capacities
High Output	80 & 115 Capacities
Extra High Output	85 & 115 Capacities
Electric Back-Up	60, 80 & 115 Capacities
Commercial Connections (For increased DHW flow)	80 & 115 Capacities (1-1/2" Dom., 1-1/4" Blr.)
Coil	Standard

*Only offered in Extra High Output models.




Stainless Steel Storage Tank

Stainless Steel Buffer Tanks




Stainless Steel Dual Coil Solar Water Heaters

30, 40, 60, 60L, 80 & 115	22, 40, 60, 80 & 115	60, 80 & 115
	N/A	
N/A	N/A	N/A
N/A	*	
	N/A	
	N/A	N/A
N/A		
60L Capacities	N/A	N/A
N/A	N/A	N/A
N/A	N/A	N/A
N/A	N/A	60, 80 & 115 Capacities
80 & 115 Capacities (1-1/2")	40, 60, 80 & 115 Capacities (1-1/4", 1-1/2", 2") 22 Capacity (1-1/4" only)	N/A
N/A	22, 40, 60, 80 & 115 Capacities	Standard



Illustrations	Model	Storage Volume	Coil Heating Surface	Dimensions (Inches)		Piping Connections N.P.T.		Max. Tank Working Pressure	Max. Coil Working Pressure	Approx. Shipping Wgt.
		Gallons	Square Feet	Height	Diameter	Domestic Water In/ Out	Boiler Water In/ Out	(psi)	(psi)	(lbs.)
STANDARD AND HO UNITS 	H2OI30UB	30	7.3	34.0	23.5	3/4	1	150	90	85
	H2OI40UB	40	7.7	44.0	23.5	3/4	1	150	90	100
	H2OI40LUB	42	7.4	36.0	28.0	3/4	1	150	90	100
	H2OI50UB	50	8.2	54.0	23.5	3/4	1	150	90	110
	H2OI60UB	60	8.6	62.0	23.5	3/4	1	150	90	125
	H2OI60LUB	60	7.7	46.0	28.0	3/4	1	150	90	120
	H2OI80UB	80	8.2	56.0	28.0	1	1	150	90	140
	H2OI115UB	115	9.1	74.0	28.0	1	1	150	90	175
	High Output Units									
	H2OI60HOUB	60	15.1	62.0	23.5	1	1	150	90	145
H2OI80HOUB	80	14.8	56.0	28.0	1	1	150	90	155	
H2OI80HOCUB	80	14.8	56.0	28.0	1-1/2	1-1/4	150	90	155	
H2OI115HOUB	115	15.6	74.0	28.0	1	1	150	90	190	
H2OI115HOCUB	115	15.6	74.0	28.0	1-1/2	1-1/4	150	90	190	
Extra High Output Units 85-XHO and 115-XHO										
H2OI85XHOCUB	87	28.7	64.0	28.0	1-1/2	1-1/2	150	90	215	
H2OI115XHOCUB	115	28.7	74.0	28.0	1-1/2	1-1/2	150	90	240	
General Information (See Installation, Operation and Maintenance Manual for complete instructions)										
HOC UNITS 		Max. First Hour Rating		Continuous Rating		Boiler Output Needed		Boiler Water Flow Through Coil		Pressure Drop Through Coil
		Gal./Hr. @		Gal./Hr. @						
		140° F	115° F	140° F	115° F	(BTU/Hr)		(Gal./Min.)		(Ft. Water)
	H2OI30UB	202	269	175	242	131,250		14.0		5.3
	H2OI40UB	221	292	185	256	138,670		14.0		5.7
	H2OI40LUB	212	251	176	215	132,000		14.0		5.3
	H2OI50UB	223	291	178	246	133,280		14.0		6.0
	H2OI60UB	262	342	208	288	155,700		14.0		6.2
	H2OI60LUB	239	310	185	256	138,570		14.0		5.7
	H2OI80UB	271	248	199	276	149,390		14.0		6.0
H2OI115UB	324	409	221	306	165,750		14.0		6.6	
High Output Units 60-HO, 80-HO, and 115-HO										
H2OI60HOUB	406	541	352	478	263,600		14.0		10.1	
H2OI80HOUB	418	551	346	479	259,640		14.0		9.9	
H2OI80HOCUB	442	584	370	512	277,070		21.0		10.5	
H2OI15HOUB	467	607	364	504	273,100		14.0		15.8	
H2OI115HOCUB	479	623	376	520	281,800		21.0		16.7	
Extra High Output Units 85-XHO and 115-XHO										
H2OI85XHOCUB	738	992	660	914	495,000		28.0		13.0	
H2OI115XHOCUB	763	1017	660	914	495,000		28.0		13.0	
Note: All ratings are based on 200° F boiler water supply and 50° F cold water inlet. See installation manual for ratings at different temperatures and flow rates. Specifications subject to change without notice.										
Standard Equipment	Smooth stainless steel coil, magnesium anode rod, factory installed stainless steel aquastat well, T & P and drain valve, welded stainless steel cold water dip tube factory installed and pressure tested, Honeywell L4080B aquastat shipped loose for field installation.									
Options	(L) Low profile models for applications with low clearances.									
	(C) Commercial models with larger tappings for higher flow rates.									
	(HO) High Output models available to meet greater demand.									
	(XHO) Extra High Output models.									
Certification/Decoding	<div> <div> H2O I 30 L UB </div> <div> I=Indirect Capacity: 30=30 Gals. 40=40 Gals. 50=50 Gals. 60=60 Gals. 80</div></div>									

Utica H₂O Stainless Steel Storage Tanks

Dimensions/Weights	Model	Storage Capacity (Gals.)	Piping Connections NPT	
			Cold/Hot Supply/Return (Inches)	Heat Source Pressure (Inches)
 <p>TOP CONNECTIONS ALL 1" NPT</p> <p>STANDARD UNITS</p>	H2OST30UB	30	1	1
	H2OST40UB	40	1	1
	H2OST60UB	60	1	1
	H2OST60LUB	60	1	1
	H2OST80UB	80	1	1
	H2OST115UB	115	1	1
	H2OST80CUB	80	1-1/2	1
	H2OST115CUB	115	1-1/2	1
Note: Max. Working pressure 150 psi for all capacities.				
General Information (See Installation, Operation and Maintenance Manual for complete instructions)				
Specifications subject to change without notice.				
Standard Equipment	Factory installed brass drain and relief valves, welded stainless steel cold water dip tube factory installed and pressure tested, Honeywell L4080B aquastat for field installation.			
Options	(L) Low profile models for applications with low clearances. (C) Commercial models available for applications with larger connections.			
Certification/ Decoding	<div><div><div><div>H2O</div><div>ST</div><div>30</div><div>L</div><div>UB</div></div><div>ST=Storage Tank</div><div>Capacity: 30=30 Gals. 40=40 Gals. 60=60 Gals. 80=80 Gals. 115=115 Gals.</div><div>L=Lowboy C=Commercial</div><div>UB=Utica Boiler</div></div><div><div>Conforms to UL STD 174 Certified to CAN/CSA STD C22.2 No. 110-94</div></div></div>			
Schematic Diagram (Typical Installation)	 <p>HOT WATER BOOSTER / STORAGE TANK DOMESTIC WATER HEATING SYSTEM / TYPICAL SCHEMATIC Note: Installation must conform to all local codes.</p>			

Dimensions & Weights			
Models	Height (Inches)	Dia. (Inches)	Shp. Wgt. (Lbs.)
H2OST30UB	34.0	23.5	75
H2OST40UB	44.0	23.5	90
H2OST60UB	62.0	23.5	115
H2OST60LUB	46.0	23.5	110
H2OST80UB	56.0	28.0	140
H2OST115UB	74.0	28.0	175
H2OST80CUB	56.0	28.0	140
H2OST115CUB	74.0	28.0	175


Utica H₂O Stainless Steel Buffer Tanks

Dimensions/Weights					Model	Storage Capacity (Gals.)	Piping Connections NPT (Inches)
<div><p>4 CONNECTIONS 1 ON RIGHT SIDE 2 ON LEFT SIDE 1 ON TOP</p></div>					H2OBT22114UB	22	1-1/4
					H2OBT40114UB	40	1-1/4
					H2OBT40112UB		1-1/2
					H2OBT402UB		2
					H2OBT60114UB	60	1-1/4
					H2OBT60112UB		1-1/2
					H2OBT602UB		2
					H2OBT80112UB	80	1-1/4
					H2OBT80114UB		1-1/2
					H2OBT802UB		2
					H2OBT115114UB	115	1-1/4
					H2OBT115112UB		1-1/2
					H2OBT1152UB		2
					H2OBT40114WCUB	40	1-1/4
					H2OBT40112WCUB		1-1/2
					H2OBT402WCUB		2
					H2OBT60114WCUB	60	1-1/4
					H2OBT60112WCUB		1-1/2
					H2OBT602WCUB		2
					H2OBT80114WCUB	80	1-1/4
					H2OBT80112WCUB		1-1/2
					H2OBT802WCUB		2
					H2OBT115114WCUB	115	1-1/4
					H2OBT115112WCUB		1-1/2
H2OBT1152WCUB	2						
Note: Max. Working pressure 60 psi for all capacities.							
General Information (See Installation, Operation and Maintenance Manual for complete instructions)							
Specifications subject to change without notice.							
Standard Equipment					Factory installed brass drain and relief valves, welded stainless steel cold water dip tube factory installed and pressure tested, Honeywell L4080B aquastat for field installation.		
Options					(WC) With Coil		
Certification/ Decoding					<div><div><div>H2O</div><div>BT</div><div>40</div><div>114</div><div>WC</div><div>UB</div></div><div><div>BT= Buffer Tank</div><div>Capacity: 22= 22 Gals. 40= 40 Gals. 60= 60 Gals. 80= 80 Gals.</div><div><div>114= 1-1/4" NPT</div><div>112= 1-1/2" NPT</div><div>2= 2" NPT</div></div><div>WC= With Coil</div><div>UB= Ulrica Boiler</div></div></div> <div><div><div><div>ETL</div><div>CM</div></div><div>LISTED</div><div>US</div></div><div>Intertek</div><div>Conforms to UL STD 174 Certified to CAN/CSA STD C22.2 No. 110-94</div></div>		
Dimensions & Weights							
Model	Height A (Inches)	B (Inches)	C (Inches)	Shp. Wgt. (Lbs.)			
H2O22BT114UB	24.5	15.0	8.0	35 (45 WC)			
H2O40BT114UB	42.0	29.0	9.0	87 (97 WC)			
H2O40BT112UB							
H2O40BT2UB							
H2O60BT114UB	42.0	29.5	9.5	115 (125 WC)			
H2O60BT112UB							
H2O60BT2UB							
H2O80BT114UB	52.0	39.5	9.5	125 (135 WC)			
H2O80BT112UB							
H2O80BT2UB							
H2O115BT114UB	72.0	59.5	9.5	160 (170 WC)			
H2O115BT112UB							
H2O115BT2UB							

UTICA H₂O STAINLESS STEEL BUFFER TANKS

- Reduces chiller or boiler short cycling
(Short cycling results in reduced operating efficiency and shorter equipment life)
- Used in systems having several low BTU cooling or heating loads calling at different times
- Full size tapings on buffer tank for peak performance (1-1/4", 1-1/2", and 2")
- Used in systems operating below the design load condition, which is most of the time.

H₂O HYDRAULICALLY DECOUPLED



Buffer Tank Sizing - Calculating Capacity

Utica H₂O buffer tanks are a simple, cost effective way to improve overall system efficiency by reducing unnecessary equipment short cycling. The recommended capacity or volume of a buffer tank is based on four variables.

- 1) The duration of the heating or cooling source "on time" (minutes). The desired length of "on time" for each run cycle depends on the type of equipment used. Heat pump and chiller manufacturers typically recommend a minimum of 5 to 10 minutes on time, and boiler manufacturers may recommend a minimum of 10 minutes "on time". Check with your equipment manufacturer. Generally, the longer the "on time", the higher the overall operating efficiency.
- 2) The minimum rate of heat input (BTU/HR). This is based on the heat pump or chiller output, or the boiler output at the minimum firing rate if the boiler has a variable input system that ramps input down as the demand decreases.
- 3) The minimum system load (BTU/HR). This is the demand placed on the system with the smallest zone calling for heat.
- 4) The allowable tank temperature rise (deg. F). This varies depending on the type of heating or cooling system used, and on the design of the distribution system. Chillers may require a tight, (6 deg. F), differential to assure good dehumidification and prevent freezing, heat pumps may require a (10 deg. F) differential to maintain a high COP, and boilers with hydronic heating distribution systems may require a differential anywhere between 10 to 40 deg. F depending on the application.

The following formula determines the tank volume:

$$V = \frac{T \times (Q \text{ heat input} - Q \text{ min. heat load})}{\text{Tank temp. rise} \times 500}$$

V = Buffer tank volume (gallons)
 Q heat source = heat source output (BTU/HR)
 Tank temp rise (deg. F)

T = desired heat source "on cycle" (min.)
 Q min. heat load = heat output to minimum load





Water to Water Heat Pump Example:

Town and Country Mechanical wants a minimum heat pump on time of 10 minutes. The heat pump output is 46,500 BTU/HR.

The smallest zone is a 7,000 BTU/HR bathroom. The allowable temperature differential is 90 to 100 deg. F for the radiant heat zones.

$$V = \frac{10 \times (46,500 - 7,000)}{(100-90) \times 500} = 79.0 \text{ Gallons minimum volume. Choose the H2O80BT buffer tank.}$$

Utica H₂O Stainless Steel Dual and Single Coil Solar Water Heaters

Dimensions/Weights	Model	Storage Capacity (Gals.)	Top Coil Heating Surface Sq. Ft.	Bottom Coil Heating Surface Sq. Ft.	Piping Connections NPT (Inches)			
<div><p>TOP COIL SUPPLY T-P VALVE TOP COIL RETURN COLD WATER IN HOT WATER OUT BOTTOM SOLAR COIL RETURN BOTTOM SOLAR COIL SUPPLY</p></div> <div><p>TOP COIL 3/8" ID THERMAL WELL 1/2" NPT RECIRC. RETURN PORT TOP HEATING COIL FOR BACKUP BOTTOM COIL 3/8" ID THERMAL WELL BOTTOM HEATING COIL FOR SOLAR</p></div> <div><p>DUAL COIL UNITS</p><p>4" X 10" ELECTRICAL BOX 3/8" ID THERMAL WELL DRAIN VALVE</p><p>ELECTRIC BACKUP UNITS</p></div>	SINGLE COIL							
	H2OI60EUB	60	N/A	8.3	1			
	H2OI80EUB	80	N/A	8.0	1			
	H2OI115EUB	115	N/A	8.9	1			
	DUAL COIL							
	H2OI60DUB	60	7.4	8.3	1			
	H2OI80DUB	80	7.4	8.0	1			
	H2OI115DUB	115	7.4	8.9	1			
	H2OI60DEUB	60	7.4	8.3	1			
	H2OI80DEUB	80	7.4	8.0	1			
	H2OI115DEUB	115	7.4	8.9	1			
	Note: Max. Working pressure 150 psi for all capacities.							
	General Information (See Installation, Operation and Maintenance Manual for complete instructions)							
	Model	Max. First Hour Rating Gal./Hr. @		Continuous Rating Gal./Hr. @		Max. Rec. Top Coil	Max. Rec. Bottom Coil	Min. Boiler Water Flow Through Coil
140° F		115° F	140° F	115° F	(Gal./Hr.)	(Gal./Hr.)	(Gal./Min.)	(Ft. Water)
SINGLE COIL								
H2OI60EUB	45.9	52.0	15.9	22.0	N/A	214	10.0	3.5
H2OI80EUB	55.9	62.0	15.9	22.0	N/A	214	10.0	3.6
H2OI115EUB	73.9	80.0	15.9	22.0	N/A	214	10.0	3.9
DUAL COIL								
H2OI60DUB	45.9	52.0	15.9	22.0	185	214	10.0	3.5
H2OI80DUB	55.9	62.0	15.9	22.0	180	214	10.0	3.6
H2OI115DUB	73.9	80.0	15.9	22.0	190	214	10.0	3.9
H2OI60DEUB	45.9	52.0	15.9	22.0	185	214	10.0	3.5
H2OI80DEUB	55.9	62.0	15.9	22.0	180	214	10.0	3.6
H2OI115DEUB	73.9	80.0	15.9	22.0	190	214	10.0	3.9
Note: All ratings are based on 180° F boiler water supply and 50° F cold water inlet. For Dual Coil units, continuous ratings shown are for the lower coil only. Specifications subject to change without notice.								
Standard Equipment	Factory installed brass drain and relief valves, welded stainless steel cold water dip tube factory installed and pressure tested, Honeywell L4080B aquastat for field installation. Removable thermal well to accept a solar control thermostat or thermistor. Dual coil units equipped with two aquastat wells which control each coil independently and built-in recirculation tapping. Units with Electric Back-Up are provided with 4" x 10" electrical box with pre-wired heating element, thermostat, and hi-limit. All electric back-up units provided with 240 volt AC, 3500 watt element.							
Options	(E) Electric Back-Up models for supplemental heating.							
Certification/Decoding	<div><div><p>Intertek</p></div><div><div><div>H2O</div><div>I</div><div>60</div><div>D</div><div>E</div><div>UB</div></div><div><div>I=Indirect</div><div>Capacity: 60=60 Gals. 80=80 Gals. 115=115 Gals.</div><div>D=Dual Coil</div><div>E=Electrical Back up (3500 Watts)</div><div>UB=Utica Boiler</div></div></div><div>Conforms to UL STD 174 Certified to CAN/CSA STD C22.2 No. 110-94</div></div>							

PN 240009329 Rev. 5/15

Contractor Assistance: 800.325.5479



P.O. Box 4729
Utica, New York 13504
tel: 315.797.1310 • fax: 315.797.3762
www.uticaboilers.com

